

# Pneumatic Fittings

## Double Banjo Body - Parallel Threaded Stem

### Technical information

**Pressure range:** -0.99 to 20 bar  
**Temperature range:** -20°C...+80°C  
**Material:** Nickel plated brass body, black acetalic resin collet  
**Seals:** PA66 washers supplied with banjo stems  
**Operating medium:** 5 micron filtered, lubricated or non-lubricated compressed air.  
**Other information:** Minimum order quantities may apply, please ask for further information.



### Double Banjo Body

| Tube Size | Stem Size | Order code   |
|-----------|-----------|--------------|
| 4         | M5        | 50510N-04-05 |
| 4         | M6        | 50510N-04-06 |
| 4         | 1/8       | 50510N-04-10 |
| 5         | 1/8       | 50510N-05-10 |
| 5         | 1/4       | 50510N-05-13 |
| 6         | 1/8       | 50510N-06-10 |
| 6         | 1/4       | 50510N-08-13 |
| 8         | 1/8       | 50510N-08-10 |
| 8         | 1/4       | 50510N-08-13 |

### Single Banjo Stem

| Thread | Order code   |
|--------|--------------|
| M5     | 51410N-05-00 |
| M6     | 51410N-06-00 |
| 1/8    | 51410N-10-00 |
| 1/4    | 51410N-13-00 |
| 3/8    | 51410N-17-00 |
| 1/2    | 51410N-21-00 |



### Single Banjo Stem - Male/Female

| Thread | Order code   |
|--------|--------------|
| 1/8    | 51440N-10-00 |
| 1/4    | 51440N-13-00 |
| 3/8    | 51440N-17-00 |



### Double Banjo Stem

| Thread | Order code   |
|--------|--------------|
| 1/8    | 51420N-10-00 |
| 1/4    | 51420N-13-00 |
| 3/8    | 51420N-17-00 |
| 1/2    | 51420N-21-00 |



### Triple Banjo Stem

| Thread | Order code   |
|--------|--------------|
| 1/8    | 51430N-10-00 |
| 1/4    | 51430N-13-00 |
| 3/8    | 51430N-17-00 |



**Impulse Automation Limited**  
**United Kingdom**  
**Company Registration 665193**