

Totalizing Counters „mini-i“ Type 634/635

Type 634: Counter with high immunity against magnetic interfere

Type 635: Counter with high shock stability



- Miniature size
- Low power consumption
- Electrical connections in standard grid
- Suitable for PCB mounting
- Machine-solderable and washable versions available
- Protection class IP 65


TECHNICAL DATA

Display	6 or 7-digit, depending on version	
Digit height	4 mm, visual	
Supply voltage V _{op}	according to order information, tolerance + -10 %	
Power consumption	Type 634 : approx. 50 mW ... 440 mW according Version Type 635 : 5...12 VDC 80 mW 24 VDC 160 mW	
Operating temperatur	- 10 ... + 50 °C	
Storage temperatur	- 40 ... + 85 °C	
El. connection	Versions .1 and .3 with solder pins, .7 and .8 with wiring posts Ø0.6 mm, cable length <30m (only Typ 634)	
Mounting	Versions .1 and .3 on PCB's, .7 with wiring posts, .8 with locating spring	
Mounting position	horizontal	
Protection class (EN 60529)	Type .1 and .3 IP 65 Housing, IP 00 Connections Type .7 and .8 IP 66 Front, IP 00 Connections Type 8 IP 40 Front in Frontpanel	
Vibro stability	Type 634 : 20 m/s ² (10...500 Hz) acc. to IEC 068-2-6 Type 635 : 30 m/s ² (10...500 Hz) acc. to IEC 068-2-6	
Shock stability	Type 634 : 2000 m/s ² acc. to IEC 068-2-27 Type 634 : 3500 m/s ² acc. to IEC 068-2-27	
General design	according EN 61010-1, EN 50178	
Contamination Level	2	
Protection	according to class II	
Overvoltage category	II	
Susceptibility to magnetic interference	Type 634 at 100 kA/m (PTB) no effect	
Maintenancefree operation	10 million pulses	
Duty cycle at 25 °C	100 %	
Weight	approx. 10 g	
Pulse length min.	50 ms	
Counting frequency max.	10 Hz	
Reset	none	





Type 634/635

Technical data

CONNECTION DIAGRAM



DIMENSIONS




Dimensions in mm


Information shown in these data sheets are for guidance purposes only, no liability is accepted for any errors or omissions. The designer or user is solely responsible for the safe and proper use of these parts, assemblies or equipment described.

ORDER INFORMATION

Type 634



Type 634



Technical data

Type 634/635



6-digits		634.1	634.3	634.7	634.8
Voltage	Ω	Ordering code	Ordering code	Ordering code	Ordering code
5 VDC	335 Ω	0 634 132	0 634 332	0 634 712	0 634 812
12 VDC	335 Ω				
	+ RV 330Ω ¹	0 634 128	0 634 328	0 634 708	0 634 808
24 VDC	335 Ω				
	+ RV 1KΩ ¹	0 634 130	0 634 330	0 634 710	0 634 810

7-digits		634.1	634.3	634.7	634.8
Voltage	Ω	Ordering code	Ordering code	Ordering code	Ordering code
5 VDC	335 Ω		0 634 667	0 634 630	
12 VDC	335 Ω				
	+ RV 330 Ω ¹	0 634 631		0 634 714	
24 VDC	335 Ω				
	+ RV 1KΩ ¹	0 634 673		0 634 713	

6-digits		635.1	635.3	635.7	635.8
Voltage	Ω	Ordering code	Ordering code	Ordering code	Ordering code
5 VDC	320 Ω	0 635 132	0 635 332	0 635 712	0 635 812
12 VDC	1860 Ω	0 635 128	0 635 328	0 635 708	0 635 808
24 VDC	3720 Ω	0 635 130	0 635 330	0 635 710	0 635 810

Connection leads 150 mm	red	1 634 008	1 634 008
	black	1 634 007	1 634 007

7-digits		635.1	635.3	635.7	635.8
Voltage	Ω	Ordering code	Ordering code	Ordering code	Ordering code
5 VDC	320 Ω	0 635 603	0 635 623	0 635 637	0 635 639
12 VDC	1860 Ω	0 635 640		0 635 652	0 635 630
24 VDC	3720 Ω	0 635 684	0 635 621	0 635 650	0 635 609

Connection leads 150 mm	red	1 634 008	1 634 008
	black	1 634 007	1 634 007

Inquire for optional mounting position and further voltages

¹ RV internal