

Logic Valves & Flow Control

Kuhnke Quick Release Couplings - Self Sealing


Technical information

Pressure range: Temperature range: Materials: Operating medium: Max. 12 bar -10°C...+70°C Brass body Neutral gases


Order connecting sockets separately, see below.

Colour	Description	Thread Connection	Order code
Blue	Master coupling blue	G1/8 male/M5 female	50.061.01
Red	Master coupling red	G1/8 male/M5 female	50.061.02
Green	Master coupling green	G1/8 male/M5 female	50.061.03
Yellow	Master coupling yellow	G1/8 male/M5 female	50.061.04
Black	Master coupling black	G1/8 male/M5 female	50.061.05
White alloy/colourless	Master coupling white, alloy colourless	G1/8 male/M5 female	50.061.06
Light green	Master coupling light green	G1/8 male/M5 female	50.061.09
Steel blue	Master coupling steel blue	G1/8 male/M5 female	50.061.10

Dimensional drawings




Socket for 6 x 1 tube with ferrule




Socket for 5 x 1 tube with ferrule

Order code: 50.065




Impulse Automation Limited United Kingdom Company Registration 665193 Socket G1/8 female

Order code: 50.062



Socket G1/8 male

Order code: 50.063



Document No: FT000 Revision 2

Information shown in these data sheets are for guidance purposes only, no liability is accepted for any errors or omissions. The designer or user is solely responsible for the safe and proper use of these parts, assemblies or equipment described.