

# Pneumatic Fittings

## Orienting Elbow (Short Stem) - Parallel Thread

### Technical information

**Pressure range:** -0.99 to 20 bar  
**Temperature range:** -20°C...+80°C  
**Material:** Nickel plated brass body, black acetalic resin collet  
**Seals:** NBR  
**Operating medium:** 5 micron filtered, lubricated or non-lubricated compressed air. Minimum order quantities may apply, please ask for further information.  
**Other information:**



Tube Size	Thread	Order code
3	M5	50116N-03-05
4	M5	50116N-04-05
4	1/8	50116N-04-10
4	1/4	50116N-04-13
5	M5	50116N-05-05
5	1/8	50116N-05-10
6	M5	50116N-06-05
6	1/8	50116N-06-10
6	1/4	50116N-06-13
8	1/8	50116N-08-10
8	1/4	50116N-08-13
8	3/8	50116N-08-17
8	1/2	50116N-08-21

Tube Size	Thread	Order code
10	1/4	50116N-10-13
10	3/8	50116N-10-17
10	1/2	50116N-10-21
12	1/4	50116N-12-13
12	3/8	50116N-12-17
12	1/2	50116N-12-21
14	3/8	50116N-14-17
14	1/2	50116N-14-21
6	M12x1	50116N-06-65
6	M12x1.25	50116N-06-66
6	M12x1.5	50116N-06-67
8	M12x1.5	50116N-08-67

**Impulse Automation Limited**  
**United Kingdom**  
**Company Registration 665193**

Information shown in these data sheets are for guidance purposes only, no liability is accepted for any errors or omissions. The designer or user is solely responsible for the safe and proper use of these parts, assemblies or equipment described.