


# Pneumatic Fittings

## Orienting Flow Regulator - Parallel Thread

### Bi-directional

#### Technical information

- Pressure range:** -0.99 to 20 bar
- Temperature range:** -20°C...+80°C
- Material:** Nickel plated brass body, black acetalic resin collet
- Seals:** NBR
- Operating medium:** 5 micron filtered, lubricated or non-lubricated compressed air. Minimum order quantities may apply, please ask for further information.
- Other information:**



Tube Size	Thread	Order code
3	M5	<b>50920N-03-05</b>
4	M5	<b>50920N-04-05</b>
4	1/8	<b>50920N-04-10</b>
5	M5	<b>50920N-05-05</b>
5	1/8	<b>50920N-05-10</b>
5	1/4	<b>50920N-05-13</b>
6	M5	<b>50920N-06-05</b>
6	1/8	<b>50920N-06-10</b>
6	1/4	<b>50920N-06-13</b>
8	1/8	<b>50920N-08-10</b>
8	1/4	<b>50920N-08-13</b>
8	3/8	<b>50920N-08-17</b>
10	1/4	<b>50920N-10-13</b>
10	3/8	<b>50920N-10-17</b>
12	3/8	<b>50920N-12-17</b>
12	1/2	<b>50920N-12-21</b>
14	1/2	<b>50920N-14-21</b>

**Impulse Automation Limited**  
**United Kingdom**  
**Company Registration 665193**