

Pneumatic Fittings

Orienting Tee (Offset Leg) - Parallel Thread

Technical information

Pressure range: -0.99 to 20 bar
Temperature range: -20°C...+80°C
Material: Nickel plated brass body, black acetalic resin collet
Seals: NBR
Operating medium: 5 micron filtered, lubricated or non-lubricated compressed air. Minimum order quantities may apply, please ask for further information.
Other information:



Tube Size	Thread	Order code
3	M5	50226N-03-05
4	M5	50226N-04-05
4	1/8	50226N-04-10
4	1/4	50226N-04-13
5	M5	50226N-05-05
5	1/8	50226N-05-10
6	M5	50226N-06-05
6	1/8	50226N-06-10
6	1/4	50226N-06-13
8	1/8	50226N-08-10
8	1/4	50226N-08-13
8	3/8	50226N-08-17
8	1/2	50226N-08-21

Tube Size	Thread	Order code
10	1/4	50226N-10-13
10	3/8	50226N-10-17
10	1/2	50226N-10-21
12	3/8	50226N-12-17
12	1/2	50226N-12-21
6	M12x1	50226N-06-65
6	M12x1.25	50226N-06-66
6	M12x1.5	50226N-06-67

Impulse Automation Limited
United Kingdom
Company Registration 665193

Information shown in these data sheets are for guidance purposes only, no liability is accepted for any errors or omissions. The designer or user is solely responsible for the safe and proper use of these parts, assemblies or equipment described.